

# Caroma®


## School Smart Standard

Vitreous China 4.5/3 litre Dual Flush  
Connector Toilet Suite

CI/SfB	(74.1)	g3
Date	December 2015	

Supersedes all previous issues

# 3.71.1



# Caroma®

## School Smart Standard

### Vitreous China 4.5/3 litre Dual Flush Connector Toilet Suite



Combined with the **Concorde Concealed** 4.5 litre pan, the **Profile** cistern is an integrated system comprising of cistern with high performance outlet valve.

- Pan:** **Concorde Concealed** 4.5 litre full flush washdown pan with open flushing rim.
- Traps:** S-trap only.
- Inlet:** 50mm back inlet 40mm key seal is available if required.
- Cisterns:** **Profile** cistern (wall fixed version) – has a free fitting lid and is suitable for domestic and light commercial applications.  
**Vandal Resistant Conversion Kit** – A simple to install conversion is available for the standard mechanism to lock lid onto the cistern, recommended for use in heavy use commercial areas. Code No.750109.
- Inlet Valve Overflow:** **Standard Bottom Entry Cistern** – available as right hand inlet which is interchangeable and incorporates Apollo inlet valve. Internal overflow only.  
**Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant.**
- Seats and Connector Plate:** The **Caravelle** black single flap vandal resistant seat is supplied with this suite. See chapter 5.01 SEATS of the Caroma Technical Manual for further details.
- Colours:** White only.
- Installation:** The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.
- Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

