



Revision: 0

Date: 21/01/2021

Supersedes all previous issues

Liano Cleanflush™ Invisi II

4.5/3 litre Dual Flush Toilet Suite with
Liano Cleanflush™ Wall Faced Rimless Vitreous China
Pan and Invisi II Cistern for Inwall, Under Counter,
Induct or Inceiling applications



cleanflush



Liano Cleanflush™ Invisi II

**4.5/3 litre Dual Flush Toilet Suite with
Liano Cleanflush™ Vitreous China
Wall Faced Rimless Pan and Invisi II
Cistern for Inwall, Under Counter, Induct
or Inceiling applications**



Combining universal design with GermGuard® Antibacterial Protection; a unique technology which kills harmful bacteria, the suite comprises of the **Liano Cleanflush™** pan and trusted Caroma **Invisi II** cistern.

The pan connection system includes the patented Caroma Uni-Orbital® Connector and adjustable flush pipe for increased installation flexibility. The Caroma Uni-Orbital® Connector extends to any position in a 50mm radius, unlike traditional connectors that only move backwards and forwards. The setout range is from 60mm – 120mm with a recommended setout of 90mm.

The adjustable flush pipe is a new feature for the Invisi II system. If the pan inlet hole is higher than the flush pipe due to floor tiling height variations, the flush pipe can be raised by up to 25mm.

Featuring rimless pan technology, the **Liano Cleanflush™** is a superior flushing system suitable for domestic and commercial applications. Incorporating several patented technologies: Caroma Flow Splitter™, Caroma Flow Balancer™ and Caroma Uni-Orbital® Connector, the Cleanflush pan is innovative and the next evolution in toilets. The Flow Splitter evenly flows water around the top of the bowl to meet at the Flow Balancer which directs the water powerfully into the sump, reducing the need for brush cleaning. The rimless pan is easy to clean and unlike traditional pan profiles, provides full visibility of any grime build up. Caroma Cleanflush provides a cleaner clean for peace of mind.

- Pan:** **Liano Cleanflush™** back inlet 4.5 litre full flush rimless pan
- Traps:** Universal trap for S or P-trap installations.
- Inlet:** 50mm back inlet for concealed cistern and flushvalve installation.
- Cisterns and Flushvalves:** **Invisi II** cistern – suitable for inwall, under counter, induct and in ceiling applications. *For push button and access plate (supplied separately) options see chapter 6.15.1 CISTERNS of the Caroma Technical Manual.*
- Fixing:** The pan can be fixed to the floor by either bedding into mortar or using the supplied D82 Concealed Fixing Bracket.
- Seats:** The **Liano** soft close toilet seat with GermGuard® Antibacterial Protection; a unique technology which kills harmful bacteria, is provided as standard with this suite. A quality solid section compression moulded toilet seat, fitted with buffers and metal hinges.
- Colours:** White only.
- Installation:** The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.
- Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.



Liano Cleanflush™ Invisi II Wall Faced Suite Inwall/Under Counter Installations

