

CAROMA

Riviere Cleanflush® Wall Faced Close Coupled Toilet Suite



The Caroma Riviere Collection features an elegant design that brings together heritage and modern style. Designed to complement a range of interior styles, including coastal, traditional, farmhouse and Hamptons, the collection enhances every space with graceful contours and refined craftsmanship.

Combining contemporary styling, industry leading rimless pan technology and GermGuard® Antibacterial Protection; a unique technology which kills harmful bacteria, Caroma Cleanflush™ is a superior flushing system suitable for domestic and commercial applications. Incorporating several patented technologies: Caroma Flow Splitter®, Caroma Flow Balancer® and Caroma Uni-Orbital® Connector, the Cleanflush pan is innovative and the next evolution in toilets. The Flow Splitter evenly flows water around the top of the bowl to meet at the Flow Balancer which directs the water powerfully into the sump, reducing the need for brush cleaning. The rimless pan is easy to clean and unlike traditional pan profiles, provides full visibility of any grime build up. Caroma Cleanflush® provides a cleaner clean for peace of mind.



- Pan:** Caroma Riviere Cleanflush® wall faced close coupled 4.5 litre full flush rimless pan.
- Traps:** Universal trap for S or P-trap installations.
- Material:** Vitreous china (pan and cistern only).
- Cisterns:** Caroma Riviere close coupled cistern - has a free fitting lid and is suitable for domestic and light commercial applications. Available with internal overflow. Available in either back entry or bottom inlet options. Cistern inlet stop valve and inlet connection is concealed within the cistern and is included (back entry version only). Vandal Resistant Conversion Kit - A simple to install conversion is available for the standard mechanism to lock lid onto the cistern, recommended for use in heavy use commercial areas. Code No.750109. **Important:** Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant. Accurate wall setout for B.S.P. 1/2" Nipple water inlet connection is essential.
- Buttons:** The cistern button is supplied in Chrome (C) but other colour options are available: Black (B), Brushed Brass (BB), Brushed Bronze (BBZ), Brushed Nickel (BN), Gunmetal Grey (GM). Code No.687071.
- Fixing:** The cistern is fixed directly to the pan with a robust concealed base fixing system without the need for wall fixing.
- Seats:** The Caroma Riviere soft close quick release thermoset toilet seat with GermGuard® Antibacterial Protection; a unique technology which kills harmful bacteria, is provided as standard with seat caps in Stainless Steel (SS). Optional seat caps are available in 3 finishes, Black (B), Brushed Brass (BB), Brushed Bronze (BBZ) or Gunmetal Grey (GM). Code No.254213.
- Colours:** White (W) and Matte White (MW).
- Installation:** The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.

White

Matte White



Product Description	Code No.	Colours
4.5/3 litre Back Entry Internal Overflow	790003	W, MW
4.5/3 litre RH Bottom Inlet Internal Overflow	790002	W, MW



Note: All height dimensions to underside of pan, make allowance for bedding when installing.

Bedding: The pan should be fixed to the floor with a sand cement mixture of 3:1 to a depth of 60mm. Do not use lime or fast drying cement in the bedding mixture. When bedded the back of the foot of the pan should be approximately 10mm above the finished floor.

Bracket fixing: The pan should be bedded with an acetic cured silicone sealant and fixed with the D82 Fixing Brackets supplied.